



IJEAST

INTERNATIONAL JOURNAL
OF ENGINEERING APPLIED SCIENCE
AND TECHNOLOGY



VOLUME : 5 ISSUE : 3 Print / Issue Publication Date: 15-Sep-2020



ISSN : 2455-2143



DOI : 10.33564/IJEAST.2020.v05i03.068

Indexed In



WWW.IJEAST.COM

editor@ijeast.com

DESIGN AND ANALYSIS OF A MICRO CD-NOZZLE FOR GENERATING SUPERSONIC FLOW

Parameshwar Banakar
 Department of Aeronautical Engg
 KLS Gogte Institute of Technology
 Belagavi, Karnataka, India

Venkatesh Kusnur
 Department of Aeronautical Engg
 KLS Gogte Institute of Technology
 Belagavi, Karnataka, India

Mayur Anvekar
 Department of Aeronautical Engg
 KLS Gogte Institute of Technology
 Belagavi, Karnataka, India

Abstract— This paper aims at design and analyses of a Convergent-Divergent nozzle in order to attain a supersonic flow at the exit of the nozzle which produces shock diamonds. Area ratios, diameters, and lengths for inlet, throat and exit are calculated mathematically with respect to a standard compressor and corresponding Mach numbers are calculated. Based on analytical results a Convergent -Divergent nozzle is designed in Catia V5 and the flow field analysis of CD nozzle is carried using Ansys fluent work bench. Both fluent results and analytical results are compared to quantify.

Keywords—Convergent-Divergent nozzle, supersonic flow, shock diamonds

I. INTRODUCTION

The nozzle is basically designed to increase the velocity of the fluid flow across it by converting heat and pressure into kinetic energy of fluid. In Aero-engines, it is used to produce efficient thrust. The fluid from subsonic velocity is accelerated to supersonic velocity using a Convergent- Divergent nozzle.

A Convergent-Divergent nozzle is a duct that is nipped in the middle, making a carefully balanced, asymmetric hourglass shape. It is used to accelerate a hot, pressurized gas passing through it to a higher supersonic speed in the axial (thrust) direction, by converting the heat energy of the flow into kinetic energy.

If the pressure & the mass flow rate through the nozzle are sufficient to reach the sonic speeds then choking occurs at the throat of a Convergent-Divergent nozzle and it produces supersonic flow downstream of throat. It means the entry pressure to the nozzle to be significantly more than the ambient at all the times. In addition, the pressure of the gas at the exit of the expansion portion of the exhaust of a nozzle must not be low. The exit pressure can be significantly below ambient pressure it exhausts into, but if it is too far below ambient, then the flow will cease to be supersonic. In practice, the nozzle exit pressure must be-around 2-3 times higher than the ambient pressure to attain supersonic flow.

The flow in the throat is sonic which means the Mach number is equal speed of sound. Downstream of the throat, the geometry diverges and the flow is isentropically expanded to a supersonic Mach number that depends on the nozzle area ratio.

If the flow is over expanded, at the nozzle exit shock diamonds are formed where as if the flow is under expanded then the expansion fans with shock diamonds will be formed.

II. METHODOLOGY




Fig.1 Methodology

Research starts with considering the capacity of a compressor of 8 bar and based on its pressure input design parameters are calculated for a Convergent-Divergent nozzle like nozzle dimensions and inlet mass flow rate, velocity and pressure. After that Convergent-Divergent nozzle is modelled using catia software.

The area relation for a given Mach number is given below:

III. INPUT AND DESIGN PARAMETERS CALCULATIONS

a) Effect of Compressors Mass Flow Rate on Design Parameters

$$\text{Mass Flow Rate, } \dot{m} = \frac{P_0 \dot{A}}{\sqrt{T_0}} (0.0414)$$

Where, $\dot{m}$ = mass flow rate in Kg/s

P_0 = Inlet Pressure in Pa

T_0 = Absolute Temperature in Kelvin

$\dot{A}$ = Throat Area in m^2

f) Calculation of Temperature Ratio

$$\frac{T_0}{T} = \left[1 + \frac{\gamma - 1}{2} M^2 \right]$$

$$\frac{T_0}{T} = 1.45$$

IV. MODELLING

b) Specification of Compressor

Model Number	TS 03 120 HN
Piston displacement	311 lpm
Free air delivery	250 lpm
Motor power	3 HP, 2.2 kW
Compressor rpm	925 rpm
Number of cylinders	2
Air receiver capacity	160 litres
Dimensions in mm	1595*500*1000

Table.1 A two-stage reciprocating compressor specifications

c) Calculation for Throat Diameter

$$0.00936 = \frac{8 * 10^5 \dot{A}}{\sqrt{300}} (0.0414)$$

$$\dot{A} = 3.915 * 10^{-6} m^2, \dot{A} = \text{Throat Area in } m^2$$

$$D = 2.49 \text{ mm}$$

d) Calculation for Exit Diameter and Area Ratio

$$\left(\frac{A}{\dot{A}} \right) = \left(\frac{\gamma + 1}{2} \right)^{-\left(\frac{\gamma + 1}{2(\gamma + 1)} \right)} \left(\frac{2 + (\gamma - 1)M^2}{2M} \right)^{\left(\frac{\gamma + 1}{2(\gamma + 1)} \right)}$$

Where A = Exit area in m^2

γ = Specific heat ratio

M = Mach number

$$\left(\frac{A}{3.915 * 10^{-6}} \right) = \left(\frac{1.4 + 1}{2} \right)^{-\left(\frac{1.4 + 1}{2(1.4 + 1)} \right)} \left(\frac{2 + (1.4 - 1)1.5^2}{2 * 1.5} \right)^{\left(\frac{1.4 + 1}{2(1.4 + 1)} \right)}$$

$$A = 7.23 * 10^{-6} m^2 \quad D = 3.041 \text{ mm}$$

e) Calculation of Nozzle Pressure Ratio (N_{pr})

$$\frac{P_0}{P_t} = \left(1 + \frac{\gamma - 1}{2} (M_t)^2 \right)^{\frac{\gamma}{\gamma - 1}}$$

$$\frac{P_t}{P_0} = 0.2724$$




Fig. 2 Catia model of Convergent-Divergent Nozzle




Fig. 3 Meshed Convergent-Divergent Nozzle

An unstructured mesh is generated with mesh size of 0.01mm with effective grid independent studies.

V. RESULTS

Analytical Results		
Mach number	P/Po	Poutput in Pascal
1.2	0.412	329600
1.5	0.272	217600
2	0.127	101600
2.2	0.093	74400
2.5	0.058	46400
2.7	0.042	33600
3.0	0.027	21600
3.2	0.020	16000
3.5	0.013	10400
4	0.0065	4800

Table.2 Mach number with respect to pressure ratios

0.412	329600	1.49
0.272	217600	1.81
0.127	101600	1.907
0.093	74400	2.02
0.058	46400	2.52
0.042	33600	2.60
0.027	21600	2.97
0.020	16000	3.02
0.013	10400	3.48
0.0065	4800	3.81

Table.3 CFD Obtained Mach numbers

VI. CONCLUSION

By calculating analytically and solving through ansys fluent software it is found that both values are matching with little deviation but the design of Convergent-Divergent nozzle was able to achieve supersonic speed with taken conditions. And also its recommended to fabricate and test the Convergent-Divergent nozzle with above said dimensions.

VII. ACKNOWLEDGEMENT

The authors are grateful to the Department of Aeronautical Engineering for its support in R&D activities and they also thank each and everyone who supported directly or indirectly for this work.

VIII. REFERENCE

- [1] George F. Hausmann (February 15, 1956.), Jet Exhaust Nozzle , Glastonbury, Conn., assignor to United Aircraft Corporation, East Hartford, Conn., a corporation of Delaware Application
- [2] John Alan Courtney Hyde, (May 11, 1959), Convergent Divergent Nozzle Assembly, assignor to Orenda Engines Limited, Village of Malton, Peel, Ontario, Canada
- [3] Joseph, Cincinnati Aerodynamic Nozzle, Ohio, (July 5, 1955), assignor to General Electric Copay, a corporation of New York
- [4] Hans P. Mehr, Mason, Ohio (Dec. 8, 1965) Convergent-Divergent Exhaust Nozzle For Supersonic Aircraft, assignor, by mesne assignments, to the United States of America
- [5] Thomas F. Tumicki, Yantic, (Sept. 23, 1964) Convergent-Divergent Co-annular Primary Nozzle Conn., assignor to United Aircraft Corporation, East Hartford, Conn., a corporation of Delaware
- [6] Norman E. Weeks, Jr., Kansas City, Kans (Feb. 4, 1958) Exhaust Nozzle Having A Flow Area Of Variable Convergency And Overgency, assignor to Westinghouse Electric Corporation, East Pittsburgh, Pa., a corporation of Pennsylvania
- [7] Vikash Babu, (2nd edition, 2015.) Fundamentals of Gas Dynamics

CFD COUNTER PLOTS




Fig. 4 Velocity contours




Fig. 5 Pressure contours

Analytical Results		CFD Results
P/Po	Poutput in Pascal	Mach number



- [8] H. Cohen, H.I.H. Saravanamuttoo, G.F.C. Rogers, Paul Straznicky, Andrew Nix(7th Edition)Gas Turbine Theory Gas Turbine Theory
- [9] R. Boyanapalli et al. (2013), "Analysis of Composite De-Laval Nozzle Suitable for rocket applications", International Journal of Innovative Technology and Exploring Engineering, 2, pp. 336- 344.
- [10] K. Pougatch, M. Salcudean, E. Chan, B. Knapper, (2008), "Modelling of compressible gas-liquid flow in a convergent-divergent nozzle", Chemical Engineering Science, 63, pp. 4176-4188
- [11] J.D. Anderson, (1996), "Compressible Flow Through Nozzles" in: "Introduction to Aerodynamics" New York: McGraw-Hill, pp. 510-530.
- [12] Q. Xiao, H.M. Tsai, D. Papamoschou, (2007), "Numerical investigation of supersonic flow separation", AIAA Journal, 45, pp. 532-541.

IJEAST

INTERNATIONAL JOURNAL
OF ENGINEERING APPLIED SCIENCE
AND TECHNOLOGY

ABOUT IJEAST

International Journal of Engineering Applied Science and Technology (IJEAST) is a peer-reviewed, open access journal that publishes high-quality research papers in the field of Engineering, Applied Science and Technology.

IJEAST aims to provide a platform for researchers, academicians, and professionals to share their innovative ideas, research findings, and practical experiences with the global scientific community.

FOCUS AREAS

- Engineering
- Applied Science
- Technology
- Innovation & Development
- Interdisciplinary Studies



PEER REVIEWED

All submissions are rigorously peer reviewed to ensure quality.



OPEN ACCESS

Free and unrestricted access to research for all.



GLOBAL REACH

Connecting researchers and professionals worldwide.



TIMELY PUBLICATION

We ensure a swift and efficient publication process.



For more information, visit our website
www.ijeast.com



INTERNATIONAL JOURNAL
OF ENGINEERING APPLIED SCIENCE
AND TECHNOLOGY

✉ editor@ijeast.com

🌐 www.ijeast.com

📍 India



2455-2143