



IJEAST

INTERNATIONAL JOURNAL
OF ENGINEERING APPLIED SCIENCE
AND TECHNOLOGY



VOLUME : 2 ISSUE : 4 Print / Issue Publication Date: 31-Mar-2017



ISSN : 2455-2143



Indexed In



WWW.IJEAST.COM

editor@ijeast.com



GEOMETRIC EFFECT AND SLIP FLOW ON MICROCHANNEL HEAT EXCHANGER A REVIEW

Krishna Kumar Ruskin
Dept. of Mechanical Engg
G.V.I.E.T, Banur, Punjab, India

Anurag Dahiya
Dept. of Mechanical Engg
G.V.I.E.T, Banur, Punjab, India

Mukesh Kumar
Dept. Mechanical Engg
G.V.I.E.T, Banur, Punjab, India

ABSTRACT: The following review paper is based on the study of heat transfer in micro channel heat exchanger. This review paper contains slip flow effect on micro channel and influence of channel geometry. To increase the performance of micro channel some points like; slip flow effect on micro channel, influence of channel geometry etc. are important to consider.

KEYWORDS: Micro channel, Heat transfer rate, Hydraulic diameter.

I. INTRODUCTION:

In 1981, the two scientists Tuckerman and Pease [1] first proposed the concept of micro channel heat sinks. Micro channel has a higher heat transfer performance low to moderate pressure drops. It has smaller geometric size. In the comparison of conventional heat exchanger micro channel has lower coolant requirement and also micro channels are operated at low cost. Many researchers have explained micro channel with their own way, criteria. According to Mehendale et al [2] the description of micro channel on the basis of the hydraulic diameter are the followings below:

Micro heat exchanger: $1\ \mu\text{m} \leq D_h \leq 100\ \mu\text{m}$

Macro heat exchanger: $100\ \mu\text{m} \leq D_h \leq 1\ \text{mm}$

Compact heat exchanger: $1\ \text{mm} \leq D_h \leq 6\ \text{mm}$

Conventional heat exchanger: $D_h \geq 6\ \text{mm}$

According to the Serizawa et al [3] the criterion for classification of micro channels as follows:

$$L \geq D_h$$

Here, L = Laplace constant

D_h = Channel diameter

NOTE: To calculate channel Hydraulic diameter, we will use the following equation-

$$D_h = 4A/P$$

Here, A = Cross-sectional area

P = Perimeter

According to Kandlikar and Grande [4] the classification of single-phase and two-phase heat exchanger by using the hydraulic diameter are the followings:

Microchannels: $10\ \mu\text{m} \leq D_h \leq 200\ \mu\text{m}$

Minichannels: $200\ \mu\text{m} \leq D_h \leq 3\ \text{mm}$

Conventional channels: $D_h \geq 6\ \text{mm}$

II. LITERATURE SURVEY

Palm [5] described that the micro channels are heat exchanger, but the classical theories (Continuum approach) can't correctly predict the heat transfer and friction factor of micro channels. On the basis of Stefan's [6] description (Micro scale system) it is not suitable to differentiate micro and mini channels by a specific diameter every time.

The applications of micro system are increasing rapidly day by day. Micro fluidic systems have many applications like –

- Micro-flow pumps
- Heat exchangers
- Valves
- Thin film coating
- Combustion
- Micro-flow sensors and



- Bio medical and bio chemical analysis instruments [7,8].
- Micro channel mostly used in micro electro mechanical systems (MEMS).

Experiments conducted by Pfahler et al.[9] , Harley et al.[10] and Arkilic et al.[11] on the transport of gases and liquids in silicon micro-machined channels deals that conventional analyses are unable to predict flow rates in micron-sized devices with any degree of accuracy .

2.1 SLIP FLOW:

It is a phenomena which is related to wall of fluid flow. It is mentioned on the basis of assumption that slip is depend on shear stress at the wall but according to the performed experiments, it is also depends on the normal stress. After investigating it is said by Rao and Rajagopal [13] that the flow field is not fully developed and rectilinear flow is not achieved if the slip velocity depends on normal stress.

Errol B.Arkilic et al. [14] mentioned on the basis of their investigation the effect of the slip velocity on the mass flow prediction of Navier-Stokes equations.

Yu and Ameel [15] studied slip flow heat transfer in micro channel and mentioned that heat transfer increases, decreases and remains unchanged compared to no slip flow condition depending upon two dimension variables.

According to Gad –el –Hak[16] the conventional no slip boundary condition impose at a solid fluid interface will begin to break before the linear stress-strain relationship becomes invalid.

Hence, the studies about the slip and no slip boundary in the micro channel heat exchanger is very important.

2.2 INFLUENCE OF CHANNEL GEOMATRY:

Some different shaped micro channels are discussed with conclusion are the followings-

On the basis of experimental studies performed by Peng and Peterson[17] it is found that that cross sectional aspect ratio had significant influence on the convective heat transfer and pressure drop in laminar and turbulent flows.

Rachkovskij et al.[18] performed his studies on heat transfer in micro tube size and relative length. Their

result shows when the size of tube then changes in heat transfer is also occurs. As the size of micro tube is decreased then the heat transfer is increased.

When Brandner et al [19] studied various micro structure cross flow heat exchangers, they comes to know that heat transfer can be enhanced by decreasing the hydraulic diameter of the micro channels.

According to Foli's et al.[20] approaches the combined CFD and analytical solution is used to optimize aspect ratio of channels. And the other approach demonstrate that performance of a micro channel depends on the operating conditions.

Ngo's et al [21] investigation is based on micro channel heat exchanger with S-shaped and zigzag fins. In this investigation he found that the micro channel with S-shaped provided 5-6 times lower pressure drop. According to the Mushtaq's et al [22] investigation on the counter flow heat exchanger with different channel cross sections like circular, squareetc.,the same volume of heat exchanger increase effectiveness and pressure drop due to increasing the number of channels. He also found the circular channels as a best performer.

In micro channel the impact of channel geometry can't be avoid. On the basis of above performed study we can conclude that it is very important to keep accurate size and shape for the design of the micro channel heat exchanger.

III. CONCLUSION:

In this review paper we have covered the factors like slip flow concept, effect of channel geometry affecting heat transfer in micro channel. With the help of above performed study we can conclude following-

1. Make such a type of micro channels which works on no slip condition as much as possible. But we can't ignore the effects of velocity –slip and temperature jump at the walls.
2. Above performed study examined the influence of channel geometry clearly (Shape and Size) on heat transfer performance. Circular shaped channels give best performance in case of counter flow micro channel heat exchanger.
3. These results are very important to design an efficient micro channel heat exchanger.



VI. REFERENCE:

- [1] D.B. Tuckerman, R.F. Pease, High performance heat sinking for VLSI, IEEE Electron. Dev. Lett. EDL 2 (1981) 126–129.
- [2] S.S. Mehendale, A.M. Jacobi, R.K. Ahah, Fluid flow and heat transfer at micro and meso-scales with application to heat exchanger design, Appl. Mech. Rev. 53(2000)175–193.
- [3] A. Serizawa, Z. Feng, Z. Kawara, Two-phase flow in micro-channels, Exp.Therm. Fluid Sci. 26 (2002) 703–714.
- [4] S.G. Kandlikar, W.J. Grande, Evolution of microchannel flow passage thermohydraulic performance and fabrication technology, Heat Transfer Eng. 24 (2003) 3–17.
- [5] B. Palm, Heat transfer in microchannel, in: Proceedings of Heat Transfer and Transport Phenomena in Microchannel, Begell House Inc., Banff, Canada, 2000. pp.54–64.
- [6] P. Stephan, Microscale evaporative heat transfer: modeling and experimental validation, in: 12th Heat Transfer Conference, Grenoble, France, 2002.
- [7] G.L. Morini, Single-phase convective heat transfer in microchannels: a review of experimental results, Int. J. Therm. Sci. 43 (2004) 631–651.
- [8] N.T. Nguyen, S.T. Wereley, Artech House, Fundamentals and Applications of Microfluidics (2002), pp. 1–10.
- [9] J. Pfahler, J. Harley, H. Bau and J.N. Zemel, “Gas and liquid flow in small channels”, DSC-Vol. 32, Micromechanical Sensors, Actuators and Systems, 49-60, ASME (1991).
- [10] J.C. Harley, Y. Huang, H.H. Bau and J.N. Zemel, “Gas flow in micro-channels”, J.Fluid Mech., 284, 257- 274 (1995).
- [11] E.B. Arkilic, K.S. Breuer and M.A. Schmidt, “Gaseous flow in micro-channels”, FEDVol.197, Application of Microfabrication to Fluid Mechanics, 57- 66, ASME (1994).
- [12] E.B. Arkilic, M.A. Schmidt and K.S. Breuer, “Gaseous slip flow in long microchannels”, J. Micro-Electro-Mechanical Systems, 6, No. 2, 167-178 (1997).
- [13] I. J. Rao and K. R. Rajgopal, The effect of the slip boundary condition on the flow of fluids in a channel, Springer-Verlag 1999.
- [14] Errol B. Arkilic, Martin A. Schmidt & Kenneth S. Breuer, Slip flow in MicroChannels, Dynamics Symposium Oxford UK, July 1994.
- [15] S.Yu, T.A. Ameel, Slip-flow heat transfer in rectangular micro channels, Int. J. Heat Mass Transfer 44 (22) (2001) 4225-4234.
- [16] M. Gad-el-Hak, “The fluid mechanics of microdevices” – The Freeman Scholar Lecture, Trans. ASME, J. Fluids Engineering, 121, 5-33 (1999).
- [17] X.F. Peng, G.P. Peterson, Convective heat transfer and flow friction for water flow in microchannel structures, Int. J. Heat Mass Transfer 39 (1996) 2599–2608.
- [18] D.A. Rachkovskij, E.M. Kussul, S.A. Talayev, Heat exchange in short microtubes and micro heat exchangers with low hydraulic losses, in: Microsystems Technologies, vol. 4, Springer, 1998, pp. 151–158.
- [19] J.J. Brandner, E. Anurjew, L. Buhn, E. Hansjosten, T. Henning, U. Schygulla, A. Wenka, K. Schubert, Concept and realization of microstructure heat exchangers for enhanced heat transfer, Experimental Thermal and Fluid Science 30 (2006) 801–809.
- [20] K. Foli, T. Okaba, M. Olhofer, Y. Jon, B. Sendhoff, Optimization of micro heat exchanger: CFD, analytical approach and multi-objective evolutionary algorithms, Int. J. Heat Mass Transfer 49 (2006) 1090–1099.
- [21] Tri Lam Ngo, Yasuyoshi Kato, Konstantin Nikitin, Takao Ishizuka, Heat transfer and pressure drop correlations of microchannel heat exchanger with S-shaped and zigzag fins for carbon dioxide cycles, Experimental Thermal and Fluid Science 32 (2007) 560–570.
- [22] Mushtaq I. Hasen, A.A. Rageb, M. Yaghoubi, Homayon Homayoni, Influence of channel geometry on the performance of a counter flow micro-Channel heat exchanger, International Journal of Thermal Sciences 48 (2009) 1607-1618.

IJEAST

INTERNATIONAL JOURNAL
OF ENGINEERING APPLIED SCIENCE
AND TECHNOLOGY

ABOUT IJEAST

International Journal of Engineering Applied Science and Technology (IJEAST) is a peer-reviewed, open access journal that publishes high-quality research papers in the field of Engineering, Applied Science and Technology.

IJEAST aims to provide a platform for researchers, academicians, and professionals to share their innovative ideas, research findings, and practical experiences with the global scientific community.

FOCUS AREAS

- Engineering
- Applied Science
- Technology
- Innovation & Development
- Interdisciplinary Studies



PEER REVIEWED

All submissions are rigorously peer reviewed to ensure quality.



OPEN ACCESS

Free and unrestricted access to research for all.



GLOBAL REACH

Connecting researchers and professionals worldwide.



TIMELY PUBLICATION

We ensure a swift and efficient publication process.



For more information, visit our website

www.ijeast.com



INTERNATIONAL JOURNAL
OF ENGINEERING APPLIED SCIENCE
AND TECHNOLOGY

✉ editor@ijeast.com

🌐 www.ijeast.com

📍 India



2455-2143