



IJEAST

INTERNATIONAL JOURNAL
OF ENGINEERING APPLIED SCIENCE
AND TECHNOLOGY



VOLUME : 5 ISSUE : 10 Print / Issue Publication Date: 25-Apr-2021



ISSN : 2455-2143



DOI : 10.33564/IJEAST.2021.v05i10.008

Indexed In



WWW.IJEAST.COM

editor@ijeast.com

QUALITATIVE AND QUANTITATIVE INTERPRETATION OF HAND-DIGITIZED AEROMAGNETIC DATA FROM IDAH

Robert Bassey Umera
 Department of Physics
 Arthur Jarvis University

Odong Peter
 Earth Sciences
 Arthur Jarvis University

Abstract— Qualitative and Quantitative interpretation of hand-digitized aeromagnetic data from Idah has been carried out by applying forward and inverse modeling technique. Qualitatively, wavelength and amplitudes of source bodies reveal lithologic contrast, basement structure and sedimentary magnetization contrast. The maximum depth to top of the magnetic source body obtained is 16.8m and minimum depth is 0.5m. The anomalous bodies' total magnetic intensity ranges from a minimum negative peak value of -153.5nT to maximum value of 162.7nT. Susceptibility values obtained reveals the presence of rocks such as granite, diabase, olivine-diabase, basalt/gabbro, quartzite and diorite. Results obtained shows that hand-digitized data competes favorably with computer digitized data


Keywords— Basement complex; Anomaly; Rock units; granite, diabase, olivine-diabase, basalt/gabbro, quartzite, diorite; suprabasement; Magnetic; Modeling; Susceptibility; basic igneous rocks

I. INTRODUCTION

Magnetometry is a potential field method of geophysical survey whose basic task in prospection geophysics is to differentiate the subsurface according to its magnetic properties. Its operative physical property is magnetic susceptibility. Magnetic survey carried out on air is normally termed aeromagnetic survey. It is a common type of geophysical survey that employs the use of a magnetometer towed behind an aircraft. The principle of the survey is similar to that carried out on land (ground magnetic survey) except that it allows coverage of larger area for regional reconnaissance. The end result being an aeromagnetic map, nowadays digitized using computer tools, upon which interpretation is made. The main use of any aeromagnetic data and their derivative maps in mineral prospecting is to make geological deduction from them Dobrin & Savit, (1988). This article however looks at the interpretation of hand digitized aeromagnetic map with a view of showing its effectiveness in interpreting aeromagnetic data.

II. THE STUDY AREA

Fig. 1.0 Geology map of the study area after Obiora et. al., (2006)



Idah is a town in Kogi state, Nigeria, which lies between latitude 7°00, N and 7°30,N and longitude 6°00E and 6°30.E. Geologically, the study area (figure 1.0) is located partly in Anambra basin and partly within the basement complex of South Western Nigeria. The geology of Nigeria is dominated by crystalline and sedimentary rocks both occurring approximately in equal proportions Woakes et. al, (1987). The crystalline rocks are made up of Precambrian basement complex and the phenerozoic rocks which occur in the eastern region of the country and the north central part of Nigeria. The Precambrian basement rocks in Nigeria consist of the migmatite, gneissic-quartzite complex dated archaean to early proterozoic (2700-2000ma). Other units include the NE-SW trending schist belts mostly developed in the western half of the country and the grantoid plutons of the older granite suit dated late proterozoic to early phanerozoic (750 – n450 Ma). Kogi, (2005) reported that the eastern flank of the state is on



the alluvium (youngest and most recent sedimentary rocks) and other sedimentary rocks which form part of cretaceous to recent sediments of Nigeria. The crystalline complex contain economic minerals such as Iron-Ore, gem-stone, quartz, feldspar and other associated minerals while the pan Africa granite/older granite contains cassiterite, tantalite, columbite, gemstones and other associated minerals.

Some researchers such as Daniel et. al, (2016), Obi et. al, (2010), Kayode (2006), Folami, (1992), have carried out interpretation of aeromagnetic data using one or more combined methods including forward and inverse modeling. This article seeks to show the effectiveness of hand-digitized data in aeromagnetic data interpretation.

III. MATERIALS AND METHOD

Aeromagnetic survey in Nigeria is mostly conducted by the Nigeria Geological Survey Agency (NGSA), the end result being a sheet of aeromagnetic map for the surveyed area and or computer digitized magnetic data for the surveyed area. Idah sheet (267) was surveyed at a flight line spacing of 500m and terrain clearance of 80m. Magnetic instrument used include air plane, toed magnetometer, recording altimeters, magnetometer stinger and digital data acquisition system, track recovery system, magnetic compensation unit and Doppler navigation system. IGRF was applied to remove geomagnetic gradient from the data.

The map was hand-digitized using a clearly calibrated ruler, HB pencil and white sheet of paper. The format of data presentation is shown in table 1.0

Table 1.0: format of hand-digitized

X	Y	Z	TMI
1.0	0	0	7025
1.2	0	0	7030

The Y & Z are set to zero while x (cm) is the corresponding value on the calibrated ruler that touches the magnetic contour line whose value is to be recorded. TMI (nT) is the total magnetic intensity. Care was taken throughout the course of hand-digitizing the map to avoid parallax error. Although hand digitization is adjudged by some geoscientists such as Bath, (1974) to be the most elementary least efficient method of digitization, however, if carefully done, its accuracy is comparable to other sophisticated methods. Also hand-digitization method does not in anyway alter the recorded values of the total magnetic intensity (TMI) on the map, thus TMI values used for the forward and inverse modeling reflects the true values obtained during field measurement. Hand-digitized data were modeled using Potent v4.11.06

geophysical software. Qualitative and quantitative data interpretation was carried out.

IV. RESULT AND DISCUSSION

RESULTS

Profile method of magnetic data presentation was adopted. Five profiles were taken on the sheet across areas of interest as shown in profile 1-5. Summary of the modeled profiles are shown in table 2.0

DISCUSSION

Qualitatively, wavelength and amplitude of an anomaly are useful tools in magnetic data interpretation. Wavelength of an anomaly is proportional to the depth of the magnetic source body that produces it. More correctly, depth is related to the horizontal distance of the slope of the anomaly Dale, (2001). Thus long wavelength is characterized by deep seated bodies while short wavelength depicts shallow sources. Amplitude on the other hand is proportional to magnetic susceptibility contrast in the rocks and it decreases with increasing distance. Amplitudes are generally divided into categories of hundreds of nT, tens of nT and ones of nT. Lithologic variation in magnetic basement or presence of igneous rocks within the sedimentary section, generally produce anomalies with the highest amplitude Dale, (2001). In summary, anomalies with amplitude of the order:

100snT maybe related to lithologic variation in basement or igneous rocks with the sedimentary section, 10snT maybe related to basement structure (suprabasement), 1snT are related to sedimentary magnetization contrast.





Figure 2.0: profile 5 showing the characteristics features of the




Consequently, a quick view of profiles 5 interms of wavelength reveals the characteristics features of the causative bodies as labeled in figure 2.0. Intermis of order of amplitudes, profile 1 has a total magnetic intensity with minimum peak value of -153nT and a maximum positive peak value of 162.7nT. This is related to lithologic variation in basement or igneous rocks with the sedimentary section. Profiles 2, 3, 4 & 5 has minimum negative values of -28.0nT, - 70.2nT, -80nT, and - 56nT, respectively to maximum positive peak values of 32.0nT, 41.2nT, 60.2nT, and 32.0nT, respectively. These are related to suprabasement. In general, the magnetic intensity of the area ranges from minimum value of - 153.5nT, to maximum value of 162.7nT. The area is marked by both high and low magnetic signatures which could be attributed to several factors such as variation in depth, difference in magnetic susceptibilities, difference in lithology and degree of strike Obiora, et. al, (2016).

Qualitatively, susceptibility values - -0.0025, 0.00262, - 0.0565, 0.0298, 0.0654, 0.0040, 0.0829 suggest the presence of rock types such as granite, diabase, olivine-diabase, basalt/gabbro, quartzite and diorite respectively. Other negative susceptibility values indicate the presence of rock types that are diamagnetic in nature. Diamagnetic materials are characterized by constant small negative susceptibilities only slightly affected by changes in temperature (Encyclopedia Britannica, 2019). Table 2.0 gives summaries of results obtained with corresponding rock types.


Profile 1




Profile 2



Profile 3



Profile 4



Profile 5






Table -1 Experiment Result

Profiles	X(m)	Y(m)	No. of bodies	K values (SI)	Dept.(m)	Type of body	Dip (deg.)	Plunge (deg)	Strike (deg.)	Suspected rock type based on value
1	8.0	-26.1	4	-0.0031	-5.8	Slap	-1.8	-18.4	-88.3	(Diamagnetic)
	22.0	-25.8		0.1134	-4.9	Slap	3.9	-0.6	-86.1	Ultramafic rocks
	34.0	1.8		0.0829	-4.0	Slap	-5.9	2.5	94.3	Diorite
	47.0	-14.2		-0.2696	-16.8	Rect. prism	11.2	2.1	-2.1	(Diamagnetic)
2	4.1	-0.4	3	0.0393	-0.8	Slap	-1.0	-1.0	4.6	(Unknown)
	6.9	-0.9		-0.1144	-1.1	Slap	0.1	-0.1	0.8	(Diamagnetic)
	1.6	-0.5		0.0040	-0.0	Rect. prism	0.2	0.0	88.1	Quartzite
3	9.4	0.0	4	-0.0017	-0.6	Slap	3.0	2.4	88.1	(Diamagnetic)
	6.8	0.1		-0.0173	-0.6	Slap	-2.2	2.0	89.9	(Diamagnetic)
	1.0	-0.8		0.0157	-2.0	Slap	1.5	1.0	-0.5	(Unknown)
	5.0	0.2		-0.0171	-0.5	Slap	0.7	1.0	0.5	(Diamagnetic)
4	2.5	-1.5	2	0.0654	-0.5	Sphere	0.0	0.0	-90.0	Basalt/gabbro
	11.3	-1.5		0.6148	-5.7	Sphere	0.0	0.0	-90.0	(Unknown)
5	0.2	-2.3	4	-0.0025	-0.6	Dyke	1.0	1.0	7.0	Granite (Diamagnetic)
	3.7	-2.9		-0.00262	-0.7	Dyke	0.0	0.0	0.9	Granite (Diamagnetic)
	7.3	-2.0		-0.0565	-0.7	Dyke	-8.0	-0.0	-178.9	Diabase (Diamagnetic)
	10.0	-2.7		0.0298	-0.9	Dyke	-11.8	-9.1	-33.0	Olivine –Diabase

V. CONCLUSION

Hand-digitized aeromagnetic map of Idah has been analyzed using forward and inverse modeling technique. Qualitative and quantitative interpretation of obtained results competes favorably with those submitted by Obiora et. al., (2006). Anomalous bodies recorded include granite, diabase, olivine-diabase, basalt/gabbro, quartzite and diorite. Susceptibility values with negative sign suggest that the area is characterized by diamagnetic materials.

VI. ACKNOWLEDGMENT

The authours are grateful to God Almighty for the success of this work. We are also grateful to the Nigeria geologic Survey Agency for providing the Map upon which hand digitisation was carried out

VII. REFERENCES

Bath M (1974) spectral analysis in geophysics. Elsevier publication co., Amsterdam

Daniel N.O. et al. (2016) Interpretation of Aeromagnetic data of Idah area in North central Nigeria using combined methods

Dobrin, M. B. & Savit, C.H. (1998) Introduction to geophysical prospecting. McGraw – Hill Book Co. Inc. New york

Egboka, B.C.E., Nwakwor G.I, and Orajaka, I.P. Implications of palæo-and neotectonics in gully erosion -prone areas of south eastern nigeria. (1990). Natural Hazards, 3:219-220 231

Folami, S. L. (1992) Interpretation of aeromagnetic anomalies in Iwaraja area, south western Nigeria, Journal of Mining. Geol 17: 179 – 176

Kayode, J.S. (2006) Ground magnetic study of Jeda – Iloko area Southwestern Nigeria and its geologic interpretation, Federal University of Technology, Nigeria.

Kogi state ministry of solid mineral development (Now ministry of special duties) (2005), Kogi state mineral Investment prospects, p49

Lowrie, W. (1997). Fundamental of applied geophysics, Cambridge, University Press.

Obi, D. A., Okereke, C.S., Obei, B.C. and George, A. M. (2010). Aeromagnetic modeling of subsurface intrusives and its implication on hydrocarbon evaluation of the lower Benue trough. *Nigeria European Journal of Scientific Research*, 47(3): 347.



Schneidegger, A.D. , and Ajakaiye, D.E. Mass movement in hilly areas (with examples from Nigeria. National hazards 9.191 -196 (1994).© Clower academic publication, printed in Netherland

Telford, W.M., Geldart, L.P. & Sheriff, R.E. (1990). Appled geophysics (2nd Edition), Cambridge, University Press, Cambridge.

Woakes, M., Ajibade C.A., Rahaman, M.A. (1987) Some metallogenic features of the Nigeria Basement, Journal of Africa science vol., pp. 655 – 664

IJEAST

INTERNATIONAL JOURNAL
OF ENGINEERING APPLIED SCIENCE
AND TECHNOLOGY

ABOUT IJEAST

International Journal of Engineering Applied Science and Technology (IJEAST) is a peer-reviewed, open access journal that publishes high-quality research papers in the field of Engineering, Applied Science and Technology.

IJEAST aims to provide a platform for researchers, academicians, and professionals to share their innovative ideas, research findings, and practical experiences with the global scientific community.

FOCUS AREAS

- Engineering
- Applied Science
- Technology
- Innovation & Development
- Interdisciplinary Studies



PEER REVIEWED

All submissions are rigorously peer reviewed to ensure quality.



OPEN ACCESS

Free and unrestricted access to research for all.



GLOBAL REACH

Connecting researchers and professionals worldwide.



TIMELY PUBLICATION

We ensure a swift and efficient publication process.



For more information, visit our website
www.ijeast.com



INTERNATIONAL JOURNAL
OF ENGINEERING APPLIED SCIENCE
AND TECHNOLOGY

✉ editor@ijeast.com

🌐 www.ijeast.com

📍 India



2455-2143